

Micro•X is a real-time, single parameter instrument that allows you to field-swap the instrument's sensor-load. Within a given sensor type, range can be swapped, a feature that is particularly useful in various measurement applications.

This instrument is available in two configurations:

- 1 - Compatible with Sound Velocity or Conductivity Xchange™ sensors
- 2 - Compatible with Temperature, Pressure, and Turbidity Xchange™ sensors, and UV•Xchange biofouling control modules

Like all other X•Series instruments, Micro•X uses Xchange™ field-swappable sensors. This means that sensor heads can be shared with other instruments, regardless of instrument size or type. Total flexibility - of instrument model, of sensor type, and of sensor range - ensures that the right instrument is always available.

Field-swappable sensors also streamline recalibration: instead of sending the entire instrument back to a recalibration centre, calibrated sensor-heads can be sent to the instrument. Changing sensors is easy: simply unscrew one sensor-head and replace it with another.



C•Xchange™



SV•Xchange™



P•Xchange™



T•Xchange™



Turbidity
•Xchange™



UV•Xchange™

Key Benefits:

- Greater flexibility: Each instrument can multi-task at multiple ranges, assuring greater usage.
- Right instrument always ready: Calibrated sensors are shared amongst all X•Series instruments, ensuring that the right instrument is always field-ready.
- Reduced downtime: Recalibrated sensors sent to the instrument means the instrument never leaves the field for recalibration.
- Reduction in transport and logistics costs: Instruments can be recalibrated without return to a calibration centre.
- Greater system redundancy: Mobility of sensor-heads and modularity of instruments minimizes the risk of downtime on the vessel.
- Streamlined management: Less time spent administering instrument recalibration and certification requirements.

Xchange™ Field Swappable Sensors:

- Field-swap any sensor with another sensor of its own type, regardless of range
- Unlike other X•Series instruments, the Micro•X is sensor specific, meaning that sensor type cannot be changed
- Each Xchange™ includes its own embedded calibration
- Sensors exchange without use of tools

Electrical:

- Communications: Factory Set RS232 or RS485
- Voltage: Externally Powered 8-26 VDC
- Current: Variable depending on sensor configuration

Sampling Modes:

- User configurable by time
- Up to 25 scans per second

Mechanical:

- Housing: Titanium to 6,000 m
- Size: 33 mm (1.3") diameter x 191 mm (7.5") OAL
- Connectors: Micro 6, Female
- Storage Temperature: -40°C to 60°C
- Operating Temperature: -20°C to 45°C

Accessories:

- Instrument suspension bar
- Instrument protection frame
- Mounting brackets
- Data/Power cable, various lengths 2m and greater

Parameter	Range	Precision	Accuracy	Resolution	Response
Xchange™					
C•Xchange™	0 to 70 mS/cm	+/-0.003mS/cm	+/-0.01mS/cm	0.001mS/cm	25ms at 1m/s flow
SV•Xchange™	1375 to 1625 m/s	+/-0.006 m/s	+/-0.025 m/s	0.001 m/s	47 microseconds
P•Xchange™	Up to 6000 dBar	+/-0.03%FS	+/-0.05%FS	0.02%FS	10 milliseconds
T•Xchange™	-2 to 32°C	+/-0.003°C	+/-0.005°C	0.001°C	100 milliseconds
Turbidity-Xchange™	up to 3000 NTU	up to +/- 0.1NTU	up to +/- 1%NTU	up to 0.01NTU	<0.7s (3s to 95%)

X•Series instruments do not come with sensor-heads; please order them separately.
Other ranges are available; please contact us. All specifications subject to change without notice.

T: +1-250-656-0771

E: sales@AMLOceanographic.com

T: +1-800-663-8721 (NA)

W: www.AMLOceanographic.com

F: +1-250-655-3655

2071 Malaview Avenue Sidney, British Columbia Canada, V8L 5X6